



NOTE: All relevant materials are complied with RoHS directive .

9461-71	
P1	P2
1	1
2	2
3	3
4	4
SHIELD	SHIELD
	24#
	RED
	WHITE
	GREEN
	BLACK
	24#

5	MOLDED PVC BLACK,LSZH	A5AC02-0751	M751
4	MOLDED PVC BLACK,LSZH	A5AC02-0751	M751
3	USB 2.0 CABLE, UL STYLE 1 TWISTED PAIR 28AWG AND 2C 24AWG, AEB(65%)HLSZH OD 4.5mm, JACKET BLACK, DRAWING: M-EMW2801P2402C-623	Xmm	M304
2	USB B MALE, GOLD FLASH ON CONTACTS, WHITE INSULATOR, SHORT A PIERCE TYPE	A1HB15-0454	M454
1	USB A MALE, GOLD FLASH ON CONTACTS, WHITE INSULATOR, SHORT A PIERCE TYPE	A1HA22-0454	M454
No.	DESCRIPTION		
PART NO. 9461-71		Revision:	
APPROVED			
CHECKED	HU		
DRAWING	XJW		
DATE	31/AUG/15	ITEM NO.	K5203.X
		Cable Length Spec: Unless Other Tolerances: 0 ~200mm ±10mm 201~1000mm ±20mm 1001 ~1500mm ±25mm 1501~2100mm ±30mm 2100mm ↓ ±40mm	

CHECKED