

INFRALAN® RJ45 patch cord U/UTP Cat.6A moulded, 500 MHz,

INFRALAN® RJ45 patch cord U/UTP Cat.6A moulded, 500 MHz,
unshielded premium patch cord with two RJ45-plugs according IEC 60603-7-41,
halogen-free, moulded crommet in slim design, cast anti-kink grommet with length imprint,
siutable for PoE IEEE802.3AF, AT und BT; IEEE802.3: 10Base-T; 100Base-T; 1000Base-T; 10GBase-T,
IEEE802.5: 16 MB; ISDN; TPDDI; ATM

Cable construction: U/UTP 4 x 2 x AWG24/7, LSZH Ø=6,0 mm
Pin assignment: 1:1, TIA/EIA 568B
Flame-retardant: IEC 60332-1
halogen-free: IEC 60754-2
Low smoke: IEC 61034
Temperature range: -20°C bis +60°C
Length: 1,0m
Color: grey

Brand: INFRALAN®
Item No.: IPK-6A-U-HFR-GR-0100

INFRALAN® RJ45 patch cord U/UTP Cat.6A moulded, 500 MHz,

INFRALAN® RJ45 patch cord U/UTP Cat.6A moulded, 500 MHz,
as described above but:

Length: X,Xm
Colour: XX

Brand: INFRALAN®
Item No.: IPK-6A-U-HFR-XX-XXXX

Example Item No.:

IPK-6A-U-HFR-XX-XXXX

-XXXX = length = „0050“ = 0,50m
-XX = color = „BL“ = blue

available in these colors:

BL = blue / GE = yellow / GN = green / GR = grey / RT = red / SW = black / WS = white

available in these lengths:

0,50m / 1,00m / 1,50m / 2,00m / 3,00m / 5,00m / 7,50m / 10,00m / 15,00m