

Label printing:


CLASS EA PIMF Patchkabel UL
 S/FTP AWG24/7,PVC,grau (length)
 CLASS EA PIMF Patchcable UL
 S/FTP AWG24/7,PVC,greyl (length)
 (PART NO)
 (ORDER NO)
 UL MARK




Remark:

- ① Cable: Cat. 6A S/FTP, Stranded Bare Copper, 4Pairs Wires, 24AWG, Jacket PVC UL Cable, OD: 6,8mm;
- ② Plug: Cat. 6A Shielded Type Plug with 3 Prongs, 50u", 8P8C, UL94-V0, Mating Cycle >1200.
- ③ Packing: IPC/PE Bag with Label.
- ④ Cableprinting: E132276-C (UL) CM 75 °C 4PR AWG24/7 CSA LL64151-C CMG 75 °C FT4 ▽ ▽ ▽ CLASS EA S/FTP PREMIUM INDUSTRIAL PATCH CORD

Testing: Standard Test.
 All materials are RoHS compliant.



ARRANGE METHOD:



- Gemäß TIA/EIA-568-C.2 Cat. 6A
- S/FTP PIMF 4x2xAWG24/7
- PVC IEC332-1-RoHS konform
- RJ45 50 µ" IEC60603-7-51
- Patentierter RJ45 für AWG24/7
- Umspritzte Knickschutzhülle
- Integrierter Klinschutz
- Für Gigabit/10Gigabit Ethernet
- Peer to peer:Cat. 6A(TIA) bis 90m
- Peer to peer:CLASS EA(ISO) bis 80m
- UL/CSA approbiert

- Follow TIA/EIA-568-C.2 Cat. 6A
- S/FTP PIMF 4x2xAWG24/7
- PVC IEC332-1-RoHS compliant
- RJ45 50 µ" IEC60603-7-51
- Patented RJ45 designed for AWG24/7
- Moulded boot
- Integrated latch protection
- For Gigabit/10Gigabit Ethernet
- Peer to peer:Cat. 6A(TIA) up to 90m
- Peer to peer:CLASS EA(ISO) up to 80m
- UL/CSA approved

WIRE CONNECTION TABLE		LENGTH		MOLD NO.	
white / orange	white / green	blue	white / brown	(4+80)1(40)1(90)	K02-113
A1	A2	A3	A4	A5	A6
B1	B2	B3	B4	B5	B6
					B7
					B8

DWG NO. K5537XX.X

TITLE
 CAT.6A S/FTP PREMIUM
 INDUSTRIAL PATCH CORD

UNIT	SCALE	SHEET
mm	1/1	1/1
DRAWN DATE	PROJ.	REV
2019/03/19		1
APPROVAL	CHECKED	DRAWN
		Cathyl Li