



9461-71	
P1	P2
1	1 RED 24#
2	2 WHITE
3	3 GREEN
4	4 BLACK 24#
SHIELD	SHIELD

ITEM NO.	L(mm)	X(mm)
K5203.0,2	200mm	180mm
K5203.0,3	300mm	280mm
K5203.0,5	500mm	480mm
K5203.1	1000mm	980mm
K5203.1,5	1500mm	1480mm
K5203.1,8	1800mm	1780mm
K5203.2,3	2300mm	2280mm
K5203.3	3000mm	2980mm
K5203.5	5000mm	4980mm
K5203.2	2000mm	1980mm

NOTE: All relevant materials are complied with RoHS directive .

REV.4 2019.02.21	ADD LENGHT	REV.3 2016.11.28	ADD LENGHT
REV.2 2016.10.14	ADD LENGHT	REV.1 2015.09.09	MODIFY LENGHT 2M OR 2.3M

PART NO. 9461-71		Revision:	
APPROVED		Cable Length Unless Other Spec. Tolerances:	
CHECKED	HU	0 ~200mm	±10mm
DRAWING	JIANG	201~1000mm	±20mm
DATE	21/FEB/19	1001 ~1500mm	±25mm
ITEM NO.	K5203.X	1501~2100mm	±30mm
		2100mm ↓	±40mm
DESCRIPTION		Q'TY	Supplier
1	USB A MALE, GOLD FLASH ON CONTACTS, WHITE INSULATOR, SHORT A PERCE TYPE	1set	M454
2	USB B MALE, GOLD FLASH ON CONTACTS, WHITE INSULATOR, SHORT A PERCE TYPE	1set	M454
3	USB 2.0 CABLE, UL STYLE 1 TWISTED PAIR 28AWG AND 2C 24AWG, AEB(65%)LSZH (D) 4.5mm, JACKET BLACK, DRAWING: NAEIWA28012402C-623	Xmm	M304
4	MOLDED PVC BLACK,LSZH	ASAC02-0751	M751
5	MOLDED PVC BLACK,LSZH	ASAC02-0751	M751

