

IES-3008 Industrial Gigabit Ethernet Switch



8 x 10/100/1000Base-T Industrial Switch



Features

- 9K Jumbo frames
- L2 wire-speed switching engine
- 8K MAC forwarding addresses
- Fanless & wide operating temperature range (-40 to +75°C)
- Dual power input (12~58 VDC) & Reverse power protection
- IP30
- Hi-POT 1.5kV
- DIN-Rail and Wall mounting options

Description

CTS IES-3008 provide 8 Gigabit Ethernet ports to fulfill the needs of the rapid growth of communication traffic in Industrial network. IES Unmanaged Series is designed for supporting not only standard industrial applications but also railway applications without complex setup to make the network truly plug-and-play.

Specification

Interface

8 x 10/100/1000Mbps (RJ-45)

Standard

IEEE 802.3 10Base-T

IEEE 802.3u 100Base-TX

IEEE 802.3ab 1000Base-T

LED

P1, P2, ALM, Link & Speed

HW Specification

- Store and forward L2 wire-speed/
non-blocking switching engine
- MAC addresses: 8K
- Jumbo frames: 9K Bytes
- Auto-negotiation in TP ports
- Auto-crossover for MDI/MDIX in TP ports

Power Requirement

- Redundant Power Input
- Reverse power protection
- Input voltage range: 12-58 VDC

Environmental Condition

- Operation: -40 ~ 75°C
- Storage: -40 ~ 85 °C
- Humidity: 5 to 95%, non-condensing

Dimension & Weight

- Ingress protection: IP30
- Dimension: 39 x 96.9 x 117.8mm (WxDxH)
- Weight: 0.39Kg
- Installation option: DIN-Rail mounting,
Wall mounting

EMC/Safety

- Vibration, shock & freefall: IEC60068-2-6,
-27, -32
- Certification compliance: CE/FCC,
EN 50121-4
- Electrical safety: CE
- EMC: FCC Part 15, CISPR 22 (EN55022)
Class A, IEC61000-4-2, -3, -4, -5, -6 (Level 3)
- RoHS and WEEE: RoHS (Pb free) and WEEE
compliant

Order Information

IES-3008 Series

MODEL	Description	Gigabit Ethernet Port	
		10/100/1000BaseTX	1G(SFP)
IES-3008	Industrial 8-Ports Gigabit Ethernet Switch	8	N/A